

**United States Patent** [19]  
**Butte**

[11] **Patent Number:** 5,075,668  
[45] **Date of Patent:** Dec. 24, 1991

[54] **HOOD ORNAMENT ALARM**

[76] **Inventor:** Charles D. Butte, 12947 San Vicente Blvd., Los Angeles, Calif. 90049

[21] **Appl. No.:** 332,357

[22] **Filed:** Mar. 31, 1989

[51] **Int. Cl.<sup>5</sup>** ..... B60Q 1/00

[52] **U.S. Cl.** ..... 340/426; 340/568;  
307/10.2

[58] **Field of Search** ..... 340/426, 429, 568, 571,  
340/686, 687; 307/10.2; 180/287; 200/61.54,  
61.55, 61.56

[56] **References Cited**

**U.S. PATENT DOCUMENTS**

1,716,373	6/1929	Ellis	200/61.55
4,137,521	1/1979	Martinez	340/426
4,293,860	10/1981	Iwata	340/429 X
4,342,373	9/1985	Hillock	340/568
4,783,352	11/1988	Kaiser, Jr.	40/591 X
4,785,144	11/1988	Fosnaugh et al.	200/61.55
4,788,550	11/1988	Chadima, Jr.	343/712

4,796,002 1/1989 Heidman, Jr. .... 340/428 X  
4,882,563 11/1989 Perlman et al. .... 340/426

*Primary Examiner*—Jin F. Ng  
*Assistant Examiner*—Brian R. Tumm  
*Attorney, Agent, or Firm*—Lyon & Lyon

[57] **ABSTRACT**

An alarm for protecting automobile or motor vehicle hood ornaments from theft or vandalism. The alarm comprises a hollow conductive body section having a spring loaded assembly positioned within the body section. One end of the spring loaded assembly is connected to the hood ornament and the other end of the assembly supports a conductive contact spaced apart from the body section whereby upon displacement of the hood ornament beyond a predetermined distance the contact is brought into engagement with the conductive body section completing the electrical circuit and sounding the vehicle's horn.

**6 Claims, 1 Drawing Sheet**

